

PRE-CERTIFIED UN 3H1 PACKAGING

5 or 6 Gallon Plastic Jerrican with Tamper Evident Neck Finish & 18mm Vent.

COMPONENT CHECK LIST:

| Quantity | Description |
|---|--|
| <input checked="" type="checkbox"/> (1) | Primary Closure: SC70EPDMTE-3/4 High Density Polyethylene 70mm Tamper Evident Buttress Threaded Closure with 3/4 Reducer. Gasket: Black EPDM 2.46" O.D. X 2.13" I.D. X 0.097"mm Thick Finish Style: 70mm Buttress |
| <input checked="" type="checkbox"/> (1) | Vent Access Closure: Air Vent Threads: 18mm Closure: Cap, PolySeal, C18/400 FRST Polypropylene, White. Liner: Laminated PE Foam. Glued In. |
| <input checked="" type="checkbox"/> (1) | Jerrican: 5 or 6 Gallon, High Density Polyethylene Finish Style: 70mm Buttress |

Note: Substitution of any of the components listed above may render the UN certification invalid

Packaging Suitability

- 1. Packaging has been certified for Packaging Group II and III liquids with specific gravities not exceeding 1.8**
- 2. The internal pressure test required for air shipment has been conducted
Test Level = 100 kPa (14.5 psi; refer to 173.24a(b)(4))**

It is the shipper's responsibility to ensure that:

- 1. The packaging is authorized for the intended hazardous material.**
- 2. The packaging is compatible with its lading, and**
- 3. The packaging meets all general shipper requirements of 173.24 and 173.24 (a).**

PRE-CERTIFIED UN 3H1 PACKAGING


5 or 6 Gallon Plastic Jerrican with Tamper Evident Neck Finish & 18mm Vent.

Packaging Assembly:

1. Once filled, the primary closure must be applied to the bottle using an application torque of 120 in-lbs (10 ft-lbs) using a torque wrench with force indicator.
2. Once filled, the packager must ensure that the vent access closure is hand tightened on the jerrican to preclude loss in shipment.

Note: Failure to follow the packaging assembly instructions listed above may render the UN certification invalid

Explanation of UN Marking



**3H1 / Y1.8 / 100 / **
USA / +AA2647**

| <u>Marking</u> | <u>Explanation</u> |
|----------------|--|
| 3H1 | Packaging Identification Code 3H1, Jerrican, Plastic, Closed Head |
| Y | Packaging has been certified at Packaging group II, Test Levels (Y) which covers Packing Group II & III liquid hazardous materials |
| 1.8 | Maximum product Specific Gravity |
| 100 | Denotes Internal Test Pressure of 100 kPa (refer to 173.24a(b)(4)) |
| ** | Insert 2 digit year the packaging was manufactured ("10" = 2010) |
| USA | Country authorizing allocation of the marking |
| +AA2647 | Packaging tested and certified by a DOT Third Party Certification Agency |