

PRE-CERTIFIED UN 3H1 PACKAGING

**5 or 6 Gallon Plastic Jerrican with Tamper Evident
FS10-10-231 Self-Venting Primary Closure**

COMPONENT CHECK LIST:

Quantity Description

- (1) Primary Closure: Rieke Flex spout Closure:
FS10-10-231 Anti-Glug Self-Venting W/ Tear away Tamper Evident Seal**

- (1) Jerrican: 5 or 6 Gallon, High Density Polyethylene**

**Note: Substitution of any of the components listed above
may render the UN certification invalid**

Packaging Suitability

- 1. Packaging has been certified for Packaging Group II and III liquids with specific gravities not exceeding 1.8.**
- 2. The internal pressure test required for air shipment has been conducted. Test Level = 100 kPa (14.5 psi; refer to 173.24a(b)(4))**

It is the shipper's responsibility to ensure that:

- 1. The packaging is authorized for the intended hazardous material.**
- 2. The packaging is compatible with its lading, and**
- 3. The packaging meets all general shipper requirements of 173.24 and 173.24 (a).**

PRE-CERTIFIED UN 3H1 PACKAGING


**5 or 6 Gallon Plastic Jerrican with Tamper Evident
FS10-10-288 Self-Venting Primary Closure**

Packaging Assembly:

- 1. Once filled, the primary closure must be applied to the bottle using a Rieke® FS 600 #01447 Crimping Tool.

Note: Failure to follow the packaging assembly instruction listed above may render the UN certification invalid

Explanation of UN Marking



**3H1 / Y1.8 / 100 / **
USA / +AA2647**

<u>Marking</u>	<u>Explanation</u>
3H1	Packaging Identification Code 3H1, Jerrican, Plastic, Closed Head
Y	Packaging has been certified at Packaging group II, Test Levels (Y) which covers Packing Group II & III liquid hazardous materials
1.8	Maximum product Specific Gravity
100	Denotes Internal Test Pressure of 100 kPa (refer to 173.24a(b)(4))
**	Insert 2 digit year the packaging was manufactured ("10" = 2010)
USA	Country authorizing allocation of the marking
+AA2647	Packaging tested and certified by a DOT Third Party Certification Agency